AB 110 ME

FEATURES

FUEL GAUGE
Fuel gauge is on the fuel tank

OHV
Over Head Valve easy to maintenance

OIL LEVEL ALARM
When the oil level is low that the engine will not start. voltage of a generator.

AVR
AVR is a device often solid state, for controlling the output

CIRCUIT PROTECTOR
Circuit Protector is a device capable of carrying and interrupting both load and fault current upto a certain rating.

HOURMETER
Hourmeter showing the product's total operating time

CHOKE SYSTEM
When the cold weather, choke system aid to operate the engine.

DUAL ELEMENT AIR FILTER

LARGE CAPACITY FUEL TANK
15-25lt
(Runtime may vary depending on fuel tank capacity)

GENERAL SPECIFICATIONS

Mono-Phase, 50 Hz, PF 1

AC Rated Power (kW)	8
Maximum Power (kW)	8,8
AC Nominal Current (A)	34,8
Voltage (V)	230
Frequency (Hz)	50
Phase Number	1
Power Factor	1
Fuel Consumption %100 (lt/h)	7,3
Fuel Consumption %75 (lt/h)	5,9
Fuel Consumption %50 (lt/h)	4,33
Noise Level (dB(A))	82,6

Manufacturer reserves the right to make change in the model, technical specifications, color, equipment, accessories and images without prior notice.
(19.07.2017)

AB 110 ME

ENGINE SPECIFICATIONS

Speed (Rpm)	3600
Power (Hp)	18
Fuel Type	Gasoline
Oil Capacity (L.)	1,7
Fuel Tank Capacity (L.)	16
Starting System	Electric/Manual

DIMENSIONS AND WEIGHT

Width (mm.)	740
Lenght (mm.)	910
Height (mm.)	750
Dry Weight (kg.)	122

Manufacturer reserves the right to make change in the model, technical specifications, color, equipment, accessories and images without prior notice.
(19.07.2017)